



LUXURY LITE

INSTALLATION: STANDARD LANDSCAPE GRASS

GRASS TYPE: LUXURY LITE

DESCRIPTION:

WARRANTY

LUXURY LITE HAS THICK, PLUSH SYNTHETIC FIBERS ARE WHICH ARE MULTI-COLORED & ADD DIMENSION TO THE LAWN.

SPECIFICATIONS: YARN POLYETHYLENE - XTREME PILE WEIGHT 80 OZ./ SQ. YD. DENIER 11,000 - 240 MICRON FILM TYPE MONOFILAMENT - 3 COLOR YARN W/ THATCH PRIMARY BACKING WEIGHT 10 OZ./ SQ.YD. SECONDARY BACKING WEIGHT 28 OZ./ SQ.YD. DIMENSIONAL STABILITY NON-WOVEN MESH BACKING CLOTH NANOBAC ANTI-BACTERIAL LAYER RESISTANT TO MICRO-ORGANISMS TOTAL WEIGHT 118 OZ/SQ.YD. FINISHED PILE HEIGHT RANGE 1-3/4" (± 1/8")(DIRECTIONAL) TUFTING GAUGE 1/21 PRIMARY BACKING DOUBLE LAYERED POLYPROPYLENE SECONDARY BACKING POLYURETHANE ROLL WIDTHS 15 EVERY 4 PERFORATION MINIMUM REQ. TUFT BIND 8 LBS SPRING GREEN & OLIVE COLORS AVAILABLE

INSTALLATION NOTES:

- I. TURF MUST BE INSTALLED AND SEAMED WITH SURROUNDING ADJACENT PIECES RUNNING IN THE SAME DIRECTION. ALL SEAMS TO HAVE SEAMING GLUE & 6" WIDE SEAMING TAPE.
- 2. TO SECURE TURF AT BASE W/6" 600 FLAT
 HEAD GALV. NAILS 3-4" ON INT. FIELD.
 PERIMETER NAILER USE I" TARPON SCRWS @
 9" O.C. ALONG PERIMETER.
- 3. RECOM'D MIN. INFILL 1/2" LB. COOL REFLECT NATURAL OR GREEN COATED SAND (OPT) AVAIL. IN 16 OR 20 MESH.
- 4. POWER BROOMING IS THE LAST STAGE OF TURF INSTALLATION.

GENERAL NOTES:

- INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH THE SPECIFICATIONS LISTED BY POLYTURF AUTHORIZED INSTALLERS.
- 2. DRAWINGS ARE FOR REFERENCE ONLY, DRAWINGS ARE NOT TO SCALE.
- 3. FOR FURTHER PRODUCT/ INSTALLATION
 INFORMATION VISIT WWW.POLYTURF.COM
 INFO@SUSTAINABLESURFACING.COM
 WWW.SUSTAINABLESURFACING.COM
 CONTACT (811) 288-0045