



## CHAMPION SPORT

INSTALLATION: CHAMPION SPORT FIELD W/ COOL REFLECT  
 GRASS TYPE: CHAMPION SPORT FIELD W/ PERVIOUS RESILENT BASE  
 DESCRIPTION:  
 MULTI-PURPOSE APPLICATIONS W/SUPERIOR PERFORMANCE  
 CHARACTERISTICS. REDUCES HEAT FACTORS BY 20°, SRI VALUE 31.  
 RECOM'D FOR MINI SPORT FACILITES, PET, PLAY, GREEN ROOFS.

### SPECIFICATIONS:

YARD #1	MONOFILAMENT COOLREFLECT FIBER
COLOR	GREEN / LIME
TOTAL DENIER	APPROX. 10,800 (1,800 x6)
DESCRIPTION	PE FORMULATION FOR SUPERIOR WEAR RESIST.
THICKNESS / FORM	APPROX. 350 MICRON RHOMBUS FORM
YARD #2	THATCH COOL REFLECT FIBER
COLOR	GREEN
TOTAL DENIER	APPROX. 8,100 (1,350 x6)
DESCRIPTION	PE FORMULATION FOR SUPERIOR WEAR RESIST.
THICKNESS/FORM	APPROX. 150 MICRON REC., ROUND EDG. FORM
TOTAL YARN FACE WT	66 OZ. / SQ.YD.
PRIMARY BACKING #1	13 PIC. MATTEX
PRIMARY BACKING #2	80 GRAM NON-WOVEN POLYESTER
PRIMARY BACKING #3	13 PIC. MATTEX
PRIMARY BACKING WT	9.60 OZ. / SQ.YD.
SECONDARY COATING	26 OZ. URETHANE/ SQ.YD.
TOTAL PRODUCT	101.60 OZ. / SQ.YD.
COLORS AVAILABLE	CONTACT POLYTURF FOR OPTIONS

### TUFTING INFORMATION

FILE HEIGHT	1.18" (± 1/8) TUFTED
STITCH RATE	AS REQUIRED
TUFTING GAUGE	3/8"
ROLL WIDTHS	15'
DRAINAGE PERFORATIONS	STANDARD

### INSTALLATION NOTES:

1. TURF MUST BE INSTALLED AND SEAMED WITH SURROUNDING ADJACENT PIECES RUNNING IN THE SAME DIRECTION. ALL SEAMS TO HAVE SEAMING GLUE & 12" WIDE SEAMING TAPE.
2. TO SECURE TURF AT PERIMETER NAILER USE 1" TARPON SCREWS @ 9" O.C. ALONG PERIMETER/ AND 2-3' ON INTERIOR.
3. POWER BROOMING IS THE LAST STAGE OF TURF INSTALLATION.

### GENERAL NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH THE SPECIFICATIONS LISTED BY POLYTURF AUTHORIZED INSTALLERS.
2. DRAWINGS ARE FOR REFERENCE ONLY, DRAWINGS ARE NOT TO SCALE.
3. FOR FURTHER PRODUCT/ INSTALLATION INFORMATION VISIT:  
[WWW.SUSTAINABLESURFACING.COM](http://WWW.SUSTAINABLESURFACING.COM)  
[INFO@SUSTAINABLESURFACING.COM](mailto:INFO@SUSTAINABLESURFACING.COM)  
 CONTACT (877) 288-0045

\*\* THESE SPECIFICATIONS ARE STANDARDS AND MAY VARY SLIGHTLY DUE TO MANUFACTURING TOLERANCES OR CONSUMER SPECIFICATIONS. THIS PRODUCT IS EXCLUSIVE TO USSA INC.