



# GARDEN GRASS

**INSTALLATION:** STANDARD LANDSCAPE GRASS  
**GRASS TYPE:** GARDEN GRASS  
**DESCRIPTION:**  
 SHORT LIGHT WEIGHT YARN FIBERS MAKE FOR LOW MAINTENANCE.

SPECIFICATIONS:	
YARN	POLYETHYLENE
PILE WEIGHT	54 OZ./ SQ. YD.
DENIER	11,000 - 320 MICRON
FILM TYPE	MONOFILAMENT W/ THATCH
PRIMARY BACKING WEIGHT	10 OZ./ SQ.YD.
SECONDARY BACKING WEIGHT	28 OZ./ SQ.YD.
DIMENSIONAL STABILITY	NON-WOVEN MESH
BACKING CLOTH	NANOBAC
ANTI-BACTERIAL LAYER	RESISTANT TO MICRO-ORGANISMS
TOTAL WEIGHT	92 OZ./SQ.YD.
FINISHED PILE HEIGHT RANGE	1-1/2" (± 1/8" X DIRECTIONAL)
TUFTING GAUGE	1/2"
PRIMARY BACKING	POLYPROPYLENE
SECONDARY BACKING	POLYURETHANE
ROLL WIDTHS	15'
PERFORATION	EVERY 4"
MINIMUM REQ. TUFT BIND	9 LBS.
COLORS AVAILABLE	SPRING GREEN & OLIVE
WARRANTY	10 YEARS

- INSTALLATION NOTES:**
- TURF MUST BE INSTALLED AND SEAMED WITH SURROUNDING ADJACENT PIECES RUNNING IN THE SAME DIRECTION. ALL SEAMS TO HAVE SEAMING GLUE & 6" WIDE SEAMING TAPE.
  - TO SECURE TURF AT BASE W/ 6" 60d FLAT HEAD GALV. NAILS 3-4' ON INT. FIELD. PERIMETER NAILER USE 1" TARPON SCRWS @ 9" O.C. ALONG PERIMETER.
  - RECOM'D MIN. INFILL 1/2" LB. COOL REFLECT NATURAL OR GREEN COATED SAND (OPT) AVAIL. IN 16 OR 20 MESH.
  - POWER BROOMING IS THE LAST STAGE OF TURF INSTALLATION.
- GENERAL NOTES:**
- INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH THE SPECIFICATIONS LISTED BY POLYTURF AUTHORIZED INSTALLERS.
  - DRAWINGS ARE FOR REFERENCE ONLY, DRAWINGS ARE NOT TO SCALE.
  - FOR FURTHER PRODUCT/ INSTALLATION INFORMATION VISIT [WWW.POLYTURF.COM](http://WWW.POLYTURF.COM) [INFO@SUSTAINABLESURFACING.COM](mailto:INFO@SUSTAINABLESURFACING.COM) [WWW.SUSTAINABLESURFACING.COM](http://WWW.SUSTAINABLESURFACING.COM) CONTACT (811) 288-0045