



LUXURY LAWN

INSTALLATION: STANDARD LANDSCAPE GRASS	
GRASS TYPE: LUXURY LAWN	
DESCRIPTION: LUXURY LAWN IS MADE OF THINNER BLADE FIBERS WITH HIGHLIGHTED GREEN AND DARK GREEN TONES FOR VARIETY.	
SPECIFICATIONS:	
YARN	POLYETHYLENE - XTREME
PILE WEIGHT	80 OZ./ SQ. YD.
DENIER	11,000 - 240 MICRON
FILM TYPE	MONOFILAMENT - 3 COLOR YARN W/ THATCH
PRIMARY BACKING WEIGHT	10 OZ./ SQ.YD.
SECONDARY BACKING WEIGHT	28 OZ./ SQ.YD.
DIMENSIONAL STABILITY	NON-WOVEN MESH
BACKING CLOTH	NANOBAC
ANTI-BACTERIAL LAYER	RESISTANT TO MICRO-ORGANISMS
TOTAL WEIGHT	123 OZ./SQ.YD.
FINISHED PILE HEIGHT RANGE	2" (± 1/8")NON-DIRECTIONAL
TUFTING GAUGE	1/2"
PRIMARY BACKING	DOUBLE LAYERED POLYPROPYLENE
SECONDARY BACKING	POLYURETHANE
ROLL WIDTHS	15'
PERFORATION	EVERY 4"
MINIMUM REQ. TUFT BIND	8 LBS.
COLORS AVAILABLE	MULTI-GREEN
WARRANTY	10 YEARS

- INSTALLATION NOTES:**
- TURF MUST BE INSTALLED AND SEAMED WITH SURROUNDING ADJACENT PIECES RUNNING IN THE SAME DIRECTION. ALL SEAMS TO HAVE SEAMING GLUE & 6" WIDE SEAMING TAPE.
 - TO SECURE TURF AT BASE W/ 6" 60d FLAT HEAD GALV. NAILS 3-4' ON INT. FIELD. PERIMETER NAILER USE 1" TARPON SCRWS @ 9" O.C. ALONG PERIMETER.
 - RECOM'D MIN. INFILL 1/2" LB. COOL REFLECT NATURAL OR GREEN COATED SAND (OPT) AVAIL. IN 16 OR 20 MESH.
 - POWER BROOMING IS THE LAST STAGE OF TURF INSTALLATION.
- GENERAL NOTES:**
- INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH THE SPECIFICATIONS LISTED BY POLYTURF AUTHORIZED INSTALLERS.
 - DRAWINGS ARE FOR REFERENCE ONLY, DRAWINGS ARE NOT TO SCALE.
 - FOR FURTHER PRODUCT/ INSTALLATION INFORMATION VISIT WWW.POLYTURF.COM INFO@SUSTAINABLESURFACING.COM WWW.SUSTAINABLESURFACING.COM CONTACT (811) 288-0045